



## DRIED SAND

### SECTION 1: MATERIAL AND SUPPLIER INFORMATION

**Product Name:** Dried Sand

**Applicable In:** Australia

**Other Names:** Dry Sand, Handy Man Dried Sand, Handy Pack Sand, Washed Sand

**Recommended Use:** Dried Sand is ideal for the preparation of cement based materials such as mortars and concrete mixes. The product is also suitable for lining bird trays, BBQ trays and adding to potting mixes.

**Company Details:** Building Products Supplies Pty Ltd  
750 Lorimer Street  
Port Melbourne, Vic 3207  
ABN 95 006 150 036

**Telephone:** VIC 03 9676 0000  
**Facsimile:** VIC 03 9646 4954

This Material Safety Data Sheet (MSDS) is issued by Building Products Supplies Pty Ltd in accordance with the Code and guidelines from the Australian Safety and Compensation Council (ASCC). The information in it must not be altered, deleted or added to. Building Products Supplies Pty Ltd will not accept any responsibility for any changes made to its MSDS by any other person or organisation. Building Products Supplies Pty Ltd will issue a new MSDS when there is a change in product specifications and/ or ASCC standards, guidelines or regulations.

### SECTION 2: HAZARDS IDENTIFICATION

**Statement Of Hazardous Nature:** This product is classified as **Hazardous** according to the criteria of the Australian Safety and Compensation Council (ASCC) Approved Criteria for Classifying Hazardous Substances (NOHSC:1008) 3<sup>rd</sup> Edition. Non-dangerous Goods

**Risk Phrases:**

R36/37: Irritating to the eyes and respiratory system.  
R48/20: Danger of serious damage to health by prolonged exposure through inhalation.

**Safety Phrases:**

S22: Do not breathe dust.  
S24/25: Avoid contact with eyes.  
S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

### SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Proportion	CAS Number
Crystalline Silica (Quartz)	>60%	14808-60-7

## SECTION 4: FIRST AID MEASURES

- Swallowed:** Rinse mouth and lips with water. Do not induce vomiting. Give water to drink. If symptoms persist, seek medical attention.
- Eyes:** Flush thoroughly with flowing water, while holding eyelids open, for 15 minutes to remove all traces. Do not attempt to remove solid particles embedded in the eye. If symptoms such as irritation, pain or redness persist, seek medical attention.
- Skin:** Remove heavily contaminated clothing immediately. Wash off skin thoroughly with water. Use a mild soap if available. Shower if necessary.
- Inhaled:** Remove to fresh air, away from dusty area. If symptoms persist, seek medical attention.
- Advice to Doctor:** Treat symptomatically.

## SECTION 5: FIRE FIGHTING MEASURES

- Flammability:** Not flammable. Does not cause dust explosions.
- Suitable extinguishing media:** Not applicable.
- Hazards from combustion products:** None.
- Special protective precautions and equipment for fire fighters:** None.
- Hazchem Code:** None Allocated

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Spills:** Spills are best cleaned up by a vacuum device to avoid generating airborne dust. Recommendations on Exposure Controls/ Personal Protection (see following sections) should be followed during spill clean-up.

## SECTION 7: HANDLING AND STORAGE

- Handling:** Handling should be in accordance with Manual handling regulations. Lifting of bags without due care and attention could result in personal injury.
- Storage:** Avoid breathing dust. Protect from moisture.
- Incompatibilities:** None
- Transport:** Transportation is by rail, road or ship – in bag form.

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Standards:

Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC: 3008(1995)]

Exposure to dust should be kept as low as practicable and below the following exposure standard:

Crystalline silica (quartz): 0.1mg/m<sup>3</sup> TWA (time-weighted average) as respirable dust.  
(< 7 microns particle equivalent aerodynamic diameter).

Total dust (of any type, or particle size): 10mg/m<sup>3</sup> TWA as inspirable dust.  
However, where a State or Territory prescribes a lower exposure standard, the lower exposure standard applies.

### Engineering Controls:

Keep exposure to dust as low as practicable, with the aim of maintaining respirable crystalline silica dust levels to below 0.05mg/m<sup>3</sup> TWA (time-weighted average). Working in the open air and external openings (such as doors and windows in buildings) generally provides adequate ventilation. Local mechanical ventilation or local dust extraction may be used, if necessary, to control airborne dust levels. If generated dust cannot be avoided follow personal protection recommendations. Where possible vacuum or wash down all gear, equipment or mobile plant prior to maintenance and repair work. If compressed air cleaning cannot be avoided, wear eye and respiratory protection, and clothing as listed below.

### Personal Protection:

#### Skin Protection:

Wash work clothes regularly. To avoid ingestion, wash hands before eating or smoking.

#### Eye Protection:

Safety glasses with side shields or safety goggles (AS/NZ 1336) or face shield should be worn.

#### Respiratory Protection:

None required if engineering and handling controls are adequate. Where engineering and handling controls are not adequate to minimize exposure to total dust and to respirable crystalline silica, personal respiratory protection may be required.

The type of respiratory protection required is dependent on the concentration of the respirable crystalline silica dust in the air and the frequency and length of exposure time. Amount of exertion required during the work and personal comfort are other considerations in choice of respirator. A suitable P1 or P2 particulate respirator chosen and used in accordance with AS/NZS 1715 and AS/NZS 1716 may be sufficient for many situations, where high levels of dust are encountered, more efficient cartridge-type powered respirators or supplied-air helmets may be necessary.

Use only respirators that bear the Australian Standards mark and are fitted and maintained correctly. Note that persons with facial hair will have difficulty in obtaining a satisfactory face seal. For alternatives see AS/NZS 1715: Selection and use of respirator protective devices.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:	Off-white to reddish tan grains.
Odour:	None
Vapour Pressure:	Not Applicable
Boiling Point / Melting Point:	MP>1200°C
Solubility in water:	Insoluble
Flammability Limits:	Not Applicable
Flash Point:	Not Applicable
Explosive Properties:	None
Specification:	Not Applicable

## SECTION 10: STABILITY AND REACTIVITY

Sand is a stable substance compatible with most other building materials.

Chemical Stability: Chemically Stable

Incompatible Materials: None

Conditions to Avoid: None

Hazardous Decomposition Products: None

Hazardous Reactions: None

## SECTION 11: TOXICOLOGICAL INFORMATION

### Health Effects

#### Acute (short term) Exposure

**Swallowed:** Unlikely under normal industrial use. Mildly abrasive to mouth and throat if swallowed. May cause nausea, stomach cramps and constipation.

**Eyes:** Irritating to the eyes. Exposure to dust may aggravate pre-existing eye conditions.

**Skin:** Dust may be irritating and drying to the skin.

**Inhaled:** Dust is mildly irritating to the nose, throat and respiratory tract and may cause coughing and sneezing.

#### Chronic (long term) Exposure- (Effects may occur after repeated or prolonged exposure)

**Eyes:** May cause irritation and inflammation of the eyes and aggravate pre-existing eye conditions.

**Skin:** Repeated contact may cause drying of the skin.

**Inhaled:** Repeated exposure to the dust may result in increased nasal and respiratory secretions and coughing. Inflammation of lining tissue of the respiratory system may follow repeated exposure to high levels of dust with increased risk of bronchitis and pneumonia. Pre-existing upper respiratory and lung diseases including asthma and bronchitis may be aggravated.

The product contains a proportion of respirable free crystalline silica. Long term occupational over-exposure or prolonged breathing-in (or inhalation) of crystalline silica dust at levels above the acceptable levels in accordance with the exposure standard carries the risk of causing serious irreversible lung disease, including bronchitis, and silicosis (scarring of the lung), including acute and/or accelerated silicosis. It may also increase the risk of other irreversible and serious disorders including scleroderma (a disease affecting the skin, joints, blood vessels and internal organs) and other auto-immune disorders.

Inhalation of dust, including crystalline silica dust, is considered by medical authorities to increase the risk of lung disease due to tobacco smoking.

Crystalline silica (inhaled in the form of quartz or cristobalite from occupation sources) has been classified by The International Agency for Research on Cancer (IARC) as carcinogenic to humans (Group 1). However the research on this is inconclusive and ASCC had not classified crystalline silica as a carcinogen.

Current research indicates there is no excess risk of lung cancer or other cancers from using these products.

Studies have shown that **smoking** increases the risk of bronchitis, silicosis and lung cancer in persons exposed to crystalline silica.

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:	Unlikely to have any impact
Persistence and Degradability:	Persistent with low degradability.
Mobility:	Low mobility would be expected in a landfill situation.

## SECTION 13: DISPOSAL CONSIDERATIONS

Dried Sand can be treated as a common waste for disposal or dumped into a landfill site in accordance with local authority guidelines. Recycling into other construction products is usually a practicable alternative. Measures should be taken to prevent dust generation during disposal and exposure and personal precautions should be observed (see section on Exposure Controls / Personal Protection).

## SECTION 14: TRANSPORT INFORMATION

Transportation is done in bulk or bag form by ship, rail or road.

UN Number:	None Allocated
Class – Subsidiary Risk:	None Allocated
Packaging Group:	None Allocated
Proper Shipping Name:	None Allocated
Hazchem Code:	None Allocated
Incompatibilities:	None

## SECTION 15: REGULATORY INFORMATION

Poisons Schedule: Not scheduled

Classified as **HAZARDOUS** according to the Australian Safety and Compensation Council (ASCC) Approved Criteria for Classifying Hazardous Substances (NOHSC:1008) 3<sup>rd</sup> Edition.

Classified as non-Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

Exposures by inhalation to high levels of dust may be regulated under the Hazardous Substances Regulations (State and Territory) as they are applicable to Respirable Crystalline Silica, requiring exposure assessment, and control of inhalation exposure below the exposure limits.

Persons who have potential for exposure to respirable crystalline silica dust above the exposure limits, may be required by Regulations to have periodic health surveillance including chest x-ray (see relevant state Government Regulations and ASCC documentation).

## SECTION 16:

## OTHER INFORMATION

For further information on this product, contact:

Telephone: [03 9676 0000](tel:0396760000)

Website: [www.bpsaust.com](http://www.bpsaust.com)

Emergency Contact Number: Poisons Information Centre [13 11 26](tel:131126)

Australian Standards References:

AS/NZS 1336 Recommended practices for occupational eye protection.

AS/NZS 1715 Selection, use and maintenance of respiratory protective devices.

AS/NZS 1716 Respiratory protective devices.

AS 2161 Industrial safety gloves and mittens (excluding electrical and medical glove).

---

### Advice Note:

The information in this document is believed to be accurate. Please check the currency of this MSDS by contacting: (03) 9676 0000

The provision of this information should not be construed as a recommendation to use this product in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Users should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace and in conjunction with other substances or products.