



Australian Builders Dried Sand is a premium quality Australian kiln dried sand that is ideal for use in any application that bacteria free pure clean white sand is required.

APPLICATIONS:

Australian Builders Dried Sand is ideally suited for many building, construction, home maintenance, garden & renovation requirements such as:

SUITABLE FOR MORTAR, CONCRETE

RENDER, GROUT MIXES

HOBBY MODELLING REQUIREMENTS

BARBECUE SAND GREASE TRAP

SWEEP INTO PAVING JOINTS

COMPACTED SAND BASE FOR PAVING

KITTY LITTER TRAY

AGRICULTURAL USES

BLENDING POTTING MIXES

PRODUCT FEATURES:

- Premium Quality
- Australian Made
- Professional Finish
- High Performance Product
- Interior & Exterior Usage

DON'T FORGET:

- Excess water will decrease strength & workability of mortar and render mixes
- Always follow Safety, Usage & Handling Directions
- Avoid creating & breathing in dry mix mortar dust
- Clean tools immediately after use with water

AVAILABLE IN

20kg bags

DIRECTIONS FOR USE:

When using to mix with cement to create Mortars and Renders. Empty contents into a wheel barrow or onto a smooth non-porous clean surface.

Mix thoroughly using the least amount of water to obtain the correct workability, (excess water will decrease strength of mortar & render mixes).

Use immediately after mixing.

Always compact your mortar thoroughly.

Fully cure your finished mortar by keeping it moist and/or covered for a least 7 days before using it.



Important Consumer Information: Please read safe handling & usage advice before opening bag.

Contents: Dried Sand.

Crystalline Silica <1%. Non-hazardous ingredients to 100%.

Note: Crystalline Silica, (quartz), is present as an impurity.

Risk: When mixed with Cement, Cement dust may cause respiratory, skin and eye irritation.

Wet cements can be irritating and corrosive to the eyes and skin; and may cause skin sensitisation (dermatitis). Repeated inhalation of dust containing crystalline silica may cause bronchitis, silicosis (scarring of the lung) and lung cancer, & increases the risk of Scleroderma.

Safety: Avoid contact with eyes and skin from both wet and dry cement. Do not breathe in dust. Wear suitable protective clothing, including gloves or barrier cream, foot wear and eye protection. Wear a P1 or P2 dust mask suitable for particulates when exposed to dust. When cutting or abrading concrete keep it wet with water to avoid creation of hazardous dust. Always wear suitable protective clothing and respiratory protection. Wash thoroughly after handling. Wash work clothes regularly.

First Aid: Irrigate eyes with plenty of water for 15 minutes and seek medical attention. If inhaled remove from dusty area. Seek medical attention if symptoms persist. Wash skin with water.

Spills/Leaks: Keep out of sewers and storm water.

Disposal: Follow above safety instructions and collect in containers for disposal as trade waste in accordance with local authority guidelines.

Manual Handling: Cement bags (16-40kg) are heavy, lifting them without due care and attention can result in personal injury. Unless you are trained in manual handling of heavy loads, it is best you share the load with another person.

DISCLAIMER: Building Products Supplies Pty Ltd products are premium quality and when used in accordance with directions, will produce consistent excellent results. However Building Products Supplies Pty Ltd accepts no responsibility for end-users inappropriate usage or faulty workmanship.

PROUDLY AUSTRALIAN MADE

Additional consumer information is listed in the material data sheet for this product, available from the manufacturer:

Building Products Supplies Pty Ltd

750 Lorimer Street Port Melbourne, Victoria, Australia. 3207. ABN 95 006 150 036

Telephone: 03 9676 0060 Facsimile: 03 9646 4954 info@bpsaust.com www.bpsaust.com